

# REVOLUTION®

## HIBINO Indoor 6mm LED Display

LVD-638

### Specifications

LED Pixel Pitch	6mm
Brightness (Max.)	1200 nit/1600 nit/3000 nit
Minimum Viewing Distance	6m
LED Type	3 in 1 SMD
Graduation	12 bit
LED Density	12,288 pixels/panel, 27,777 pixel/sqm, 2,580 pixel/sqf
Interface	360Mbps SDI (DTL-523)
Viewing Angle	Horizontal 120° (50% brightness, normal mask) Vertical 120° (50% brightness, normal mask)
Life Time	50,000h (50% brightness)
Refresh Rate	960Hz (60Hz input), 800Hz (50Hz input) *adjustment with DTL-523
Processor	<a href="#">DLC-612</a> , DLC-118HD, DLC-106
Power	AC 100V-240V/400W (1200 nit)
Temperature	Operation 0~40°C(32~104°F) Storage -20~60°C(-4~140°F)
Dimensions	W768mm (30.2") x H576mm (22.7") x D163mm (6.4")
Weight	Approx. 37kg (81.6lb) (1,200nit)

#### REVOLUTION

Marca registrada nº471517  
De Rui Ferreira & Daniel Tibério, Lda.  
TEL: 239 947143 / TM – 963521683/ 91 2391840